

**BASIC CHARACTERISTICS:**

Pieces name:	BLUEBELL GRIS 23X120 (PRC)
Size (cm.):	23X120
Colour:	GRIS
Series name:	BLUEBELL
Family:	GLAZED PORCELAIN STONEWARE

TECHNICAL CHARACTERISTICS:

Fabrication process:	Dry pressed ceramic tile	
Absorption group (ISO 13006):	Bla	
Finish:	Glazed (GL)	
Body:	Standard Body	
Surface Finish:	Matt	
Work size (mm):	2300 x 1200 x 10,5	
Aesthetic classification and shade variations:	V.1	
Different design number:	16	
Facial dimension range and surface quality:	Complies with the standard	UNE EN ISO 10545-2

PHYSICAL CHARACTERISTICS:

Water absorption:	E ≤ 0.5	UNE EN ISO 10545-3
Braking strenght (S):	> 1300N	
Flexural tensile strenght (N/mm ²):	≥35 N/mm ²	UNE EN ISO 10545-4

IMPORTANT NOTES:

Before fixing tiles, please check the shade, calibre and choice. Claims regarding these items cannot be accepted once the materials has been fixed. Protecting the product during placement and appropriate cleaning after grouting and other work are part of a correct fitting process. For more information, see: www.argentaceramica.com For more information, visit to www.argentaceramica.com/downloads. The stated weight is approximate, it may vary up to 5% depending on the model, the variation may be greater for products with relief. Document with commercial information and cannot be used either judicially or administratively without the express permission of Argenta Ceramica S.L. The color of the tile of this technical data is for guidance only and may differ from the actual tile color. ☒

Lineal thermal expansion between 20° to 100°C	Complies with the standard	UNE EN ISO 10545-8
Thermic shock resistance:	Complies with the standard	UNE EN ISO 10545-9
Crazing resistance:	Complies with the standard	UNE EN ISO 10545-11
Durability; Freeze - thaw cycle:	Complies with the standard	UNE EN ISO 10545-12
Scratch hardness according to Mohs:	8	UNE EN 67-101-92
Slipperiness:	Anti-slip class 3	UNE - ENV 12633:2003

CHEMICAL PROPERTIES:

Resistance to chemicals and pool treatment products:	Complies with the standard	
Resistance to High concentration acids and bases:	Minimum HB	UNE EN ISO 10545-13
Resistance to Low concentration acids and bases:	Minimum LB	
Resistance to staining:	Complies with the standard	UNE EN ISO 10545-14

CE MARKING:



004CPR-PR/01-7-2013

IMPORTANT NOTES:

Before fixing tiles, please check the shade, calibre and choice. Claims regarding these items cannot be accepted once the materials has been fixed. Protecting the product during placement and appropriate cleaning after grouting and other work are part of a correct fitting process. For more information, see: www.argentaceramica.com For more information, visit to www.argentaceramica.com/downloads. The stated weight is approximate, it may vary up to 5% depending on the model, the variation may be greater for products with relief. Document with commercial information and cannot be used either judicially or administratively without the express permission of Argenta Ceramica S.L. The color of the tile of this technical data is for guidance only and may differ from the actual tile color. ☒